

High Integrity Pressure Protection System

ELECTRONIC HIPPS Series



DESCRIPTION

The QUAM HIPPS Series is a **SIL 3 capable System**, designed according to IEC 61508 and IEC 61511 standards, used to protect downstream equipment against overpressure or upset conditions coming from the Upstream.

THE HIPPS



GENERAL APPLICATION

Electronic HIPPS System considerably reduces overpressure process risks and environmental impacts with lower weight and cost for piping and vessels downstream the system itself. No need to install relief devices.

KEY FEATURES

No need to install a by-pass line

QUAM Actuated Gate Valve is designed to be opened against full differential pressure

Independent certification

3rd party SIL3 certificate

Tight Shut-off

Leakage requirements as per Class VI of ANSI/ FCI 70-2

Fugitive Emission

In accordance with ISO 15848-2

Fire Safe Design

Gate valve are tested to API 6FA

Fast Action

Valve stroking time for safe action: less than 2 sec.

Integrated Design

Any part of the safety system is internally designed and manufactured

SYSTEM ARCHITECTURE

QUAM Electronic HIPPS System includes:

Electronic Logic Solver

Electronic Logic Solver detects signals from the Transmitters and closes the final element de-energizing the solenoid valves in order to discharge the power fluid from the cylinder by the quick exhaust valve, this action strokes the main valve to the safety position. The solenoid valves are installed in series with suitable voting logic to achieve SIL3 requirement. Partial stroke test is available for inspection upon request.

Initiators (Pressure Transmitters)

Pressure transmitters are configured 2oo3 voting logic and are engineered to detect the pipeline pressure and send analogic 4-20 mA signal to Logic Solver

Final Element (Actuated Gate Valve)

The actuated gate valves close the downstream line and is usually configured in 1oo2 voting logic to achieve SIL3 requirement.

BENEFITS

Single Source

For Valve, Actuator & Control System

Better Sealing Feature

Of Slab Gates against Ball or Axial Flow

Overall Dimensions

Smaller than other valve types

Heavy Duty Design

For long life service

Easy & Safe Maintenance

100% ITALIAN MANUFACTURING

SAFETY INTEGRITY LEVEL GUIDE

According to **IEC 61508**, in order to meet **SIL 3** requirements, the system must comply with both probabilistic requirements and architectural constraints.

Safety Integrity Level	PFD (Avg. Probability of Dangerous Failure on Low Demand Mode)	PFH (Avg. Frequency of Dangerous Failure on High Demand Mode)
SIL1	$\geq 10E-02$ to $< 10E-01$	$\geq 10E-06$ to $< 10E-05$
SIL2	$\geq 10E-03$ to $< 10E-02$	$\geq 10E-07$ to $< 10E-06$
SIL3	$\geq 10E-04$ to $< 10E-03$	$\geq 10E-08$ to $< 10E-07$
SIL4	$\geq 10E-05$ to $< 10E-04$	$\geq 10E-09$ to $< 10E-08$